

Manufacturers of High Performance Floor Coatings and Re-Surfacing Screeds









Epoxy Products Limited Unit 7 Haviland Road Ferndown Ind. Estate Wimborne Dorset BH21 7RZ

Phone: 01202 891899 Fax: 01202 896983 Email: sales@epoxyproducts.co.uk Web: www.epoxyproducts.co.uk

# **Cleaning Solvent**

- **▲** Excellent Tool Cleaner
- **▲** Rapid Removal of wet Epoxy Resins
- **▲** Excellent Tool Cleaner after using Epoxies
- Removes Oil Patches from Concrete



#### THE RANGE

We have been manufacturing a range of cleansers for concrete, stone and brick substrates for over three decades.

For fast effective cleaning and degreasing of painted concrete, bare concrete and to remove cement splashes from brickwork. These powerful industrial grade cleansers are extremely good value for money.

### **CLEANING SOLVENT**

A blend of solvents for the rapid cleansing of all hand tools and mixing equipment having used epoxy resin based products. For releasing the build up of "resin tack" from the trowel when applying Epoxy Mortar. For quick instant removal of oil and grease spillages from concrete and painted floors.

Available in 5 litre tins.

http://www.epoxyproducts.co.uk/concretecleaner.html



Manufacturers of High Performance Floor Coatings and Re-Surfacing Screeds

















Epoxy Products Limited Unit 7 Haviland Road Ferndown Ind. Estate Wimborne Dorset BH21 7RZ

Phone: 01202 891899 Fax: 01202 896983 Email: sales@epoxyproducts.co.uk Web: www.epoxyproducts.co.uk

## **Cleaning Solvent**

## **DESCRIPTION**

**CLEANING SOLVENT** is a carefully formulated blend of solvents designed for the rapid removal of wet epoxy resin materials from hand tools and mixing equipment. As an excellent cleanser to release the build up of "resin tack" from the face of the application trowel. To remove oil and grease and others forms of contamination from bare concrete, painted floors, ceramic tiles and most epoxy resin based flooring. It has outstanding cutting strength and will quickly and efficiently restore contaminated floors back to their original pristine condition.

**USES**: For the general cleaning of all hand tools and mixing equipment when handling epoxy resin based materials. For the cleaning of the trowel face to release the build up of tack during the application of PATCHING MORTAR, EPOXY MORTAR and EPOXY SCREED HD flooring. For the rapid removal of oil and grease patches from concrete, painted floors, ceramic tiles and most Epoxy Resin flooring systems. Excellent localised patch degreaser prior to subsequent floor painting.

**APPLICATION**: When cleaning tools and equipment pour a small amount into a small plastic bucket and apply with a small paint brush. When releasing the build up of tack from the trowel apply using a cloth or small paint brush. Always keep the screw cap on the tin and store carefully away from naked flames.

**CAUTION:** This product is flammable and must be used with extreme caution.

**HEALTH AND SAFETY**: Always read the Health & Safety Data Sheet prior to handling this product. Avoid skin and eye contact. If eye contact is made rinse thoroughly with cold clean water for 20 minutes and seek immediate medical advise.

## **PRODUCT DATA**

#### **APPEARANCE / ODOUR**

Clear, colourless liquid with mild alcoholic odour

#### **SPECIFIC GRAVITY @ 20°C**

0.830 - 0.840

### **FLASH POINT**

This product is highly flammable with a flash point of 12°C Min.

#### STODAGE

Flammable/Combustible. Keep away from heat, flames and direct sunlight.

## **PERSONAL PRECAUTIONS**

Avoid breathing vapours. Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Extinguish all ignition sources. Do not smoke when handling this product. Provide good ventilation when handling and confine all spillages. Read Health and Safety Data Sheet prior to handling this product.

### **PACK SIZE**

5 Litre tin

Whilst Epoxy Products Limited endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it can not, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification or information given.