

# PRODUCT DATA SHEET

## GEO-DRAIN QUATTRO

Product Code: DMS006



[info@deltamembranes.com](mailto:info@deltamembranes.com)

[www.deltamembranes.com](http://www.deltamembranes.com)

01992 523 523

**Delta Geo-Drain Quattro is an external cavity drain membrane with four layers designed to be externally applied as a protective layer installed over a flexible waterproof coating like Koster Deuxan 2C.**

It has very high compression strength, protecting the primary waterproofing during backfilling. When used externally below ground, the GeoDrain membrane can deal with hydrostatic water pressure, creating a cavity for any water to pass into and filter down to a land drain. It can then be taken away from the building by either natural means or by a pumping station.



### BENEFITS

- Easy and quick to apply straight off the roll
- Effectively prevents the buildup of water pressure on the waterproof coating
- Improved slip performance
- High resistance to compression due to a special dimple design
- Outstanding drainage capacity for dealing with unusually large quantities of water
- Rot-proof



### SPECIFICATION

- NBS Specification J40 295A flexible sheet tanking/damp proofing



### ASSOCIATED PRODUCTS

- Koster Waterproofing
- Geo-Drain Clips
- Delta MS Profile
- Delta Haftangel (self- adhesive pins)

# PRODUCT DATA SHEET

## GEO-DRAIN QUATTRO

Product Code: DMS006

### TECHNICAL DATA

|                        |                                |
|------------------------|--------------------------------|
| Stud Height            | 9mm (approx)                   |
| Roll Size              | 2m x 12.5m                     |
| Material               | High Density Polyethylene      |
| Compressive Strength   | 400 kN/m <sup>2</sup> (approx) |
| Temperature Resistance | -30°C to +80°C                 |

