




High Performance Floor
Coatings and
Re-Surfacing Screeds

EPOXY SCREED



DRYFIX EPOXY SCREED HEAVY DUTY

- **Outstanding Early Strength**
- **Non-Porous, Good Slip Resistance**
- **Solvent Free - Virtually Odourless**
- **Excellent Chemical Resistance**



EPOXY SCREED HEAVY DUTY is a three part, solvent free epoxy resin, formulated to provide a thin resurfacing screed for concrete floors. This non-porous, slip resistant, easy to clean finish is ideal for areas that demand a tough hard wearing and decorative surface.

USES: Industrial floor topping screeds in dairies, bakeries, breweries, food preparation areas, engineering shops, chemical stores, kitchens, sports changing rooms and all other areas that demand a hygienic and durable permanent surface.

PREPARATION: Surfaces must be dry and free from grease, oil and other forms of contamination. Remove any loose materials and sweep clean. Cleaning is imperative. For large areas vacuum shot blasting is recommended. For small areas ensure the concrete is clean, sound and dry. For chemical cleaning use our Concrete Cleaner.

CONCRETE REPAIRS: Fill deep holes and badly worn concrete prior to priming with Patching Mortar or Epoxy Filler. Allow expansion joints to follow through the new floor.

CONCRETE TEMPERATURE: Ensure the concrete temperature to be resurfaced is constantly above 10°C during the application and throughout the hardening period.

PRIMING: The concrete must be primed with Epoxy Sealer the day prior to applying the Epoxy Screed HD. For small areas use Tack Primer immediately prior to laying. Working across the floor in strips you can lay on top of the Tack Primer while it is wet.

Alliance Remedial Supplies Limited

Unit 11-12 Regent Trade Park, Gosport, Hampshire, PO13 0EQ

Tel: 01329 235252, Email: sales@arsstore.co.uk, Web: allianceremedialsupplies.co.uk

VAT: 119 914 303, Co Reg: 07814823



High Performance Floor
Coatings and
Re-Surfacing Screeds

EPOXY SCREED



MIXING: Empty the contents of Pack “B” (Hardener) into Pack “A” (Resin) and mix thoroughly together by hand. Pour the mixed Resin/Hardener into the large bucket containing Pack “C” (Filler) and stir using either:- for large quantities use a “Forced Action Mixer” or for smaller quantities an electric drill and paddle attachment. Continue to mix until uniform in colour for at least 3 minutes.

APPLICATION: Pour the mixed material onto the primed floor. Apply immediately using a steel trowel to the required depth, normally between 3mm and 6mm. Occasionally clean the face of the trowel using CLEANING SOLVENT to release the build up of resin tack.

HEALTH & SAFETY: Read the Health & Safety Data Sheet prior to handling this product.

COVERAGE: 10 kg will cover 1m² at 5mm depth.

POT LIFE CURING TIME: When fully mixed, approximately 25-30 minutes @ 20°C. Extended pot life at lower temperatures. Reduced period at high temperatures. Light traffic after 24 hours @ 20°C. Suitable for fork trucks after 48 hours @ 20°C. Full cure, strength and chemical resistance after 7 days.

CHEMICAL RESISTANCE: Resistant to spillages of many chemicals commonly met within industry. Contact Technical Services for more advice.

PROPERTIES			
STRENGTH	AFTER 24 HOURS	3 DAYS	7 DAYS
Tensile Strength	10.34 MN/m ²	17.20 MN/m ²	24.12 MN/m ²
Compressive Strength	31.86 MN/m ²	50.20 MN/m ²	91.72 MN/m ²
Flexural Strength	-	18.96 MN/m ²	22.40 MN/m ²

POT SIZES: 10kg & 20kg - Combined weight of Resin, Hardener and Filler.

COLOURS: Available in a range of colours.

Whilst Alliance Remedial Supplies Limited endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it can not, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification or information given.

Alliance Remedial Supplies Limited

Unit 11-12 Regent Trade Park, Gosport, Hampshire, PO13 0EQ

Tel: 01329 235252, Email: sales@arsstore.co.uk, Web: allianceremedialsupplies.co.uk

VAT: 119 914 303, Co Reg: 07814823