



SumpFlushHP



SYSTEM OVERVIEW



One powerful free-standing automatic pump



Access cover, solid top, locking, galvanised steel, FACTA AA



1 1/4" Class E PVC pipework



110 mm inlet



1 1/4" Class E PVC discharge



50 mm cable duct

The SumpFlushHP is a fully automatic wastewater pumping system suitable for pumping surface and/or ground water to a higher level when gravity drainage is not possible and/or economical to install.

It features a powerful submersible pump for high head (up to 12 m) and flow (up to 4 l/s) applications.

The system provides up to 65 litre storage capacity depending inlet depth. It can accept waste from car parks, car washes, floor areas, down pipes, cavity membrane systems or similar.

It is not suitable for receiving foul waste. Contact our Sales Team for advice on a suitable foul water packaged pumping stations for your property.

The system consists of a polyethylene tank, a powerful automatic wastewater submersible pump and solid top, locking, galvanised steel access cover (FACTA AA).

It discharges to solvent welded 1 1/4" Class E PVC. Optional discharge reducer kits can increase external discharge diameter to 1 1/2" or 2" to reduce friction loss.

It is easy to install as inlets can be positioned to your site's requirements. Inlet information to be supplied at time of order, or can be drilled on site.

KEY FEATURES

- Powerful vortex pump for high head and flow
- Up to 65 litres storage capacity
- Compact chamber for limited space installations
- Ideal for an extension, outbuilding, basement or similar
- 350 mm x 350 mm clear opening
- Variable inlet positions to suit site
- A range of battery backup systems are available
- A range of alarms and remote alerts are available
- Quick and simple to install

WASTE TYPE



Grey



Ground



Surface



Storm

For groundwater and surface water applications where inflow cannot be controlled, twin pump systems complete with a high level alarm and battery backup system should be used, in accordance with BS 8102:2022 and PCA Guidelines. High level alarms and battery backup systems can be purchased to your specification.


RECOMMENDED ACCESSORIES

| | | | | | | |
|--|-------------------------------|---------------------------------------|--|---|--|--|
| AquaSafe Alarm (Mini) #22070 | UPS 3000 #29000 | PowerShield 1500 #37507 | Battery backup, 24 V Please call | Inlay access cover #18011 | Additional inlet 110 mm 50 mm #17010 #17012 | Discharge reducer kit 1 1/2" to 1 1/4" 2" to 1 1/4" #8203 #8202 |
|--|-------------------------------|---------------------------------------|--|---|--|--|

All our products can be customised to your requirements. For more information and advice please call our Sales Team on 01442 211554.

SumpFlushHP


TYPICAL INSTALLATION



- A. Structurally-reinforced virgin tank-grade polyethylene chamber.
- B. Non-return valve.
- C. Float bracket for optional high level alarm mini float.
- D. 1½" Class E PVC plain female discharge for solvent welding to high pressure PVC (reducer kits available).
- E. Socket union for simple pump removal during servicing.
- F. Galvanised steel, solid top, locking, access cover, FACTA AA (inlay access cover available).
- G. 50 mm cable duct positioned to site requirements.
- H. 110 mm inlet positioned to site requirements (additional inlets available).
- I. Powerful automatic 240 V submersible pump.

CHAMBER DIMENSIONS

Shows indicative capacities from lowest inlet invert.




Permitted connection positions

| | | | |
|----------------|------------------------|----------------------------|---------------------|
| Discharge only | Inlet location allowed | Cable ducts and vents only | No drilling allowed |
|----------------|------------------------|----------------------------|---------------------|

PUMP SPECIFICATIONS

| | |
|----------------------|-----------|
| Number of pumps | One |
| Impellor type | Vortex |
| Control | Automatic |
| Power supply | 230 VAC |
| Rated current | 4.9 A |
| Motor rating (P2) | 500 W |
| Revolutions per min. | 2800 |
| Discharge size | 1½" |
| Free passage | 10 mm |
| Max. vertical output | 12.5 m |
| Max. flow rate | 4.0 l/s |
| Max liquid temp. | <40 °C |
| Cable length | 5 m |
| Weight | 6.9 kg |



CHAMBER SPECIFICATIONS

| | |
|--------------------------|-------------------------|
| Internal pipework | 1½" OD Class E PVC |
| Discharge pipework | 1½" OD Class E PVC |
| Lifting eyes | No |
| Maximum storage capacity | 65 litres |
| Chamber material | Tank-grade polyethylene |
| Dimensions (Ø x H) | 600 x 600 mm |
| Clear opening | 350 x 350 mm |

ACCESS COVER

| | |
|------------------------|-------------------|
| Material | Galvanised steel |
| Cover type | Solid top |
| Locking | 4 screws |
| Loading | FACTA AA |
| Clear opening (H x W) | 300 x 300 mm |
| Dimensions (H x W x D) | 370 x 370 x 47 mm |

DELIVERING PUMPED AND DRAINAGE SOLUTIONS FOR OVER 30 YEARS

Packaged pumping stations

Waste water pumping systems

Macerators and macerating toilets

Floor mounted pumping stations

Fat, oil and grease separating systems


Rainwater harvesting systems

Battery backup systems

Adoptable pumping stations

Submersible pumps

Accessories



We provide pumped and drainage products and services to the public and private sectors, including residential, commercial, hospitality and retail.

We are proud of the long-term relationships we have built with our clients and partners, delivering cost effective, robust and dependable products and services.

12-MONTH GUARANTEE

Your products are protected by a 12-month guarantee. Please refer to our Terms and Conditions at www.edincare.com

HOW TO ORDER

Order online at www.edincare.com
Call Sales on 01442 211554
Email sales@edincare.com

PROJECT SERVICES

- Project design
- Site surveys
- Installations
- Refurbishments

AFTERSALES SERVICES

- Planned servicing
- Emergency call outs
- Commissioning
- Monitoring

DRAINAGE SERVICES

- Tankering
- Jetting
- Drainage CCTV
- Surveys
- Cleaning and de-scaling
- Structural repairs
- Excavations
- Root cutting

www.edincare.com

- Discover our products and services
- Order products online
- Case studies and articles
- Brochures and technical documents

Protect your property with an Edincare Service Agreement

As with all pumped and drainage systems, regular maintenance is essential to ensure optimum performance and minimal downtime. Our Service Agreements comprises planned preventive maintenance visits at an agreed frequency, we also service other manufacturers' equipment regardless of type, make and age.

- ✓ Validates your building insurance
- ✓ Reduces the risk of failure
- ✓ Increases the life expectancy of your equipment
- ✓ Priority callouts and 24/7 out-of-hours service
- ✓ Reduced rates for emergency call outs
- ✓ Flexible payment options (Direct Debit)



+44 (0)1442 211554
info@edincare.com

www.edincare.com
edincarepumps

Unit 8, Heron Business Park, Eastman Way,
Hemel Hempstead, Hertfordshire, HP2 7FW

Part of the Edincare Group of Companies www.edincaregroup.com



Our policy is one of continuous product improvement, we reserve the right to change specifications and prices without prior notice. All information is given in good faith. No responsibility can be accepted for errors, omissions or incorrect assumptions. © Omni Pump International Ltd t/a Edincare Pumps & Edincare Drains. All rights reserved.