

FLUX HR Plus+



FLUX HR Plus+

Single room heat recovery unit with easy to use remote control

Alternate flow ("push-pull") unit will automatically vary the airflow depending on the mode selected.

IMPROVES INDOOR AIR QUALITY

Better health and reduced heating costs.



Helps tackle the causes of condensation and mould.



Advanced remote control brings further comfort and efficiency settings for the perfect atmosphere.



Very low running costs and also helps save money on your heating.



The magnetic latching removable fascia makes filter cleaning easy.

01384 275771

info@eltatrade.co.uk

www.eltatrade.co.uk





FEATURES & BENEFITS

- 2 sizes available to suit application.
- **Constant airflow** effectively deals with condensation and mould issues.
- Automatic management of the inversion time (in comfort mode) optimises acoustic and thermal comfort.
- Smart humidity control.
- **Easy and safe maintenance** thanks to a magnetic fan faceplate system.
- **Simplified synchronisation** of up to 10 units; thanks to a dedicated communication protocol, the units automatically synchronise when they are wired to each other.
- Automatic anti-frost protection prevents frost from building up on the heat exchanger.

- Free cooling mode prevents heat exchange when not needed i.e. during the summer.
- **Remote control operation** with the following functions:
 - Airflow direction (alternate, extract only or intake only).
 - Free cooling.
 - ON/OFF and speed (5 options).
 - Comfort/efficiency mode.
 - Boost speed.
 - Filter reset.
- **5 year warranty,** for full details, visit www.eltatrade.co.uk.

PERFORMANCE DATA

FLUX HR Plus+	100	150							
Airflow L/s	25/21/17/14/10	60/50/40/30/20							
Power W	3.5/3/2.5/2/2	6/4.5/3.5/2.5/2							
Sound Pressure dB(A) @ 3m	27/23/18/14/9	29/24/20/14/10							
Volts	220-240								
Hertz	50/60								
Max Ambient Temperature °C	50								
Degree of Protection	Wall: IPX4	Ceiling: IPX2							

Data shown at high to low speed settings.
For full technical data, please refer to **www.eltatrade.co.uk.**

DIMENSIONS

Model	A	В	С	D	E	F	G	н	1	J	K
FLUX HR 100 Plus+	218	77.5	300-570	110	164	117.5	39	23	124	44	26.5
FLUX HR 150 Plus+	218	77.5	300-570	159	218	117.5	39	23	124	44	26.5

Dimensions in mm.





