



High Performance Floor
Coatings and
Re-Surfacing Screens

EPOXY FLOORING

DRYFIX EPOXY LINE PAINT

- **Solvent Free - Virtually Odourless**
- **Withstands Fork Trucks**
- **Rapid Cure / Hardening**
- **Long Lasting Performance**



EPOXY LINE is a two-part, heavy duty epoxy resin line paint. It has excellent chemical and abrasion resistance. Epoxy Line will provide long term performance and outlast other conventional line paints by many years. It is suitable for both interior and exterior applications.

USES: An long lasting line paint to designate gangways, isles, footpaths and hazard identification for factory floors, warehouses, workshops, plant rooms, goods in/out areas, in fact any floor that requires traffic designation areas. This product is suitable for areas that are heavily trafficked by fork lift trucks, pallet trucks and pedestrians.

PREPARATION: Surfaces must be clean, dry, sound and free from grease, oil and other forms of contamination. Epoxy Line will bond exceptionally well to existing epoxy coated floors. Best results are achieved when you abrade the existing flooring surface to form a key. Epoxy Line can be applied to previously painted floors providing the existing floor paint is sound. Secure paper masking tape to designate the lineage and remove the tape soon after you have applied the coating.

MIXING: Empty the contents of (Hardener) Pack B into the (Resin) Pack A. Mix well using a pallet knife or flat blade for approximately 3 minutes. Ensure you reach the sides and bottom of the tin during mixing. Having mixed thoroughly, the entire contents must be used within 40 minutes.

Alliance Remedial Supplies Limited

Unit 11-12 Regent Trade Park, Gosport, Hampshire, PO13 0EQ

Tel: 01329 235252, Email: sales@arsstore.co.uk, Web: allianceremedialsupplies.co.uk

VAT: 119 914 303, Co Reg: 07814823





High Performance Floor
Coatings and
Re-Surfacing Screens

EPOXY FLOORING



APPLICATION: Apply the Epoxy Line immediately after mixing by brush or radiator roller. Apply evenly between the masking tape. Anti-slip aggregates or fine dry sand can be sprinkled upon the Epoxy Line while still wet, to provide additional slip resistance particularly for wet areas.

HEALTH AND SAFETY: Always read the separate Health and Safety Data Sheet prior to handling this product.

COVERAGE: 750ml should cover up to 37.5 linear metres for a 50mm wide line depending upon the site conditions that prevail. Reduced coverage for textured and porous substrates.

CONDITIONING: Ideally store the Epoxy Line Paint in warm conditions for 24 hours prior to using. Should the product be stored in cold temperatures then reduced coverage rates will result.

POT LIFE: When fully mixed, approximately 40 minutes @ 20°C. Extended pot life at lower temperatures, Reduced pot life at higher temperatures.

CURING /HARDENING TIME: Tack free after 4 hours @ 20°C. Suitable for fork trucks after 4 hours @ 20°C Full hardness after 7 days. Do not use at temperatures below 4°C.

CHEMICAL RESISTANCE: Resistant to spillages of most chemicals commonly met within industry.

SLIP RESISTANCE: This product will become slippery should it become wet. Additional slip resistance can be achieved by lightly sprinkling dry sand upon the 'wet' coating during its application.

COLOURS: White, Safety Yellow, Safety Red, Safety Green, Mediterranean Blue and Black. Colour matching service is available.

Whilst Alliance Remedial Supplies Limited endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it can not, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification or information given.

Alliance Remedial Supplies Limited

Unit 11-12 Regent Trade Park, Gosport, Hampshire, PO13 0EQ

Tel: 01329 235252, Email: sales@arsstore.co.uk, Web: allianceremedialsupplies.co.uk

VAT: 119 914 303, Co Reg: 07814823