



# Epoxy Line Coating

## 750ml

- > Solvent Free — Virtually Odourless
- > Withstands Fork Trucks
- > Rapid Cure / Hardening
- > Long Lasting Performance

**DESCRIPTION:** Epoxy Line is a two-part, heavy duty epoxy resin line paint. It has excellent chemical and abrasion resistance. Epoxy Line will provide long term performance and outlast other conventional line paints by many years. It is suitable for both interior and exterior applications.

**USES:** An long lasting line paint to designate gangways, isles, footpaths and hazard identification for factory floors, warehouses, workshops, plant rooms, goods in/out areas, in fact any floor that requires traffic designation areas. This product is suitable for areas that are heavily trafficked by fork lift trucks, pallet trucks and pedestrians.

**PREPARATION:** Surfaces must be clean, dry, sound and free from grease, oil and other forms of contamination. Epoxy Line will bond exceptionally well to existing epoxy coated floors. Best results are achieved when you abrade the existing flooring surface to form a key. Epoxy Line can be applied to previously painted floors providing the existing floor paint is sound. Secure paper masking tape to designate the lineage and remove the tape soon after you have applied the coating.

**MIXING:** Empty the contents of (Hardener) Pack B into the (Resin) Pack A. Mix well using a pallet knife or flat blade for approximately 3 minutes. Ensure you reach the sides and bottom of the tin during mixing. Having mixed thoroughly, the entire contents must be used within 40 minutes.

**APPLICATION:** Apply the Epoxy Line immediately after mixing by brush or radiator roller. Apply evenly between the masking tape. Anti-slip aggregates or fine dry sand can be sprinkled upon the Epoxy Line while still wet, to provide additional slip resistance particularly for wet areas.

**HEALTH AND SAFETY:** Always read the separate Health and Safety Data Sheet prior to handling this product.

**COVERAGE:** 1 Litre should cover up to 50 linear metres for a 50mm wide line depending upon the site conditions that prevail. Reduced coverage for textured and porous substrates.

**CONDITIONING:** Ideally store the EPOXY LINE in warm conditions for 24 hours prior to using. Should the product be stored in cold temperatures then reduced coverage rates will result. POT LIFE When fully mixed, approximately 40 minutes @ 200C. Extended pot life at lower temperatures, Reduced pot life at higher temperatures.

**CURING /HARDENING TIME:** Tack free after 4 hours @ 200C. Suitable for fork trucks after 4 hours @ 200C Full hardness after 7 days. Do not use at temperatures below 40C.

**CHEMICAL RESISTANCE:** Resistant to spillages of most chemicals commonly met within industry.

**SLIP RESISTANCE:** This product will become slippery should it become wet. Additional slip resistance can be achieved by lightly sprinkling dry sand upon the 'wet' coating during its application.

**TOOL CLEANING:** Clean all tools with water and detergent.

**COLOURS:** White, Safety Yellow, Safety Red, Safety Green, Mediterranean Blue and Black. Colour matching service is available.