



Sovereign DekMate Exterior Wood Oil & Decking Stain



DekMate Exterior Wood Oil and Decking Stain has been designed to enhance the natural beauty of new and pre-existing timber decking, sheds and fences.

Product Codes

Colour	5 Litres
Oak	30612035
Brown	30612039
Clear	30612040
Cedar	30612041
Green	30612042
Pine	30612043

Description

DekMate Exterior Wood Oil and Decking Stain has been designed to enhance the natural beauty of new and pre-existing timber decking, sheds and fences.

It replaces natural wood oils that are lost over time and provides a water repellent finish. Containing water repellents, pigments, UV absorbers and a broad spectrum of fungicides. Protection from water penetration reduces warping, swelling and splitting. UV absorbers protect against the harmful rays of the sun, which cause greying and splitting of the timber.

Form Supplied: Ready to use liquid

Pack Sizes: 5 Litres

Colour Range: Clear, Oak, Green, Cedar, Brown, Pine

Contains: White Spirit, Linseed oil, Preservatives

Properties

Suitable for all types of softwoods and hardwoods to give a decorative wood finish. The clear grade can also be used on timber garden furniture..

Preparation

Surfaces to be treated must be clean, dry and free from dust, dirt, grease and flaking coatings. Mould and mildew should first be cleaned using Sovereign Masonry Sterilising Wash. If a deck to be treated requires cleaning, particularly if pressure washing is used, allow three days after cleaning before applying Exterior Wood Oil. Moisture content of the timber must be below 18%. Do not apply if rain is forecast in the next 24 hours and only apply in temperatures between 5 °C and 30°C.

Do not use knotting solution, allow knots to 'bleed out' through the coating and remove resin with a scraper when necessary. Un-treated external timber and cut ends should be treated with Sovereign Timber Preservative prior to application.

Shake the can well for at least a minute to redistribute any settled pigments. Decant enough product into a clean, solvent-resistant container for immediate use. Do not return unused material to the original tin as this could contaminate all the contents.



Sovereign DekMate Exterior Wood Oil & Decking Stain

Technical
Data Sheet

330

USAGE

Apply by brush, roller or decorating pad, making sure the product is distributed completely and evenly. Do not allow the liquid to pool in grooves. Apply a second coat once the first has become dry enough to walk on. During application pay particular attention to ensuring the end grain and joints are fully sealed. Do not walk on the decking after the second coat for at least 24 hours

DRYING TIMES

Typically touch dry and re-coatable within 2 - 4 hours and hard dry overnight. Foot traffic after 24 hours

MAINTENANCE

Timber should be inspected regularly to ensure integrity of coating. When recoating becomes necessary thoroughly clean and dry the surface and apply one or two coats of Exterior Wood Oil & Decking Stains.

LIMITATIONS

Do not use the coloured versions on timber furniture and do not use indoors. It is recommended to try a test area first as final appearance is dependent on application method, type of wood and the presence of previous treatments.

Do not apply by spray. Do not use near water courses and keep away from plants, trees and animals during application

COVERAGE

Depending on the type and condition of timber, approximately 4m² to 6m² per litre

Storage: Between 5°C - 30°C.

Shelf Life: A minimum of 12 months in unopened containers.

HEALTH & SAFETY

- ! Irritating to eyes and skin.
- ! Prolonged repeated contact may cause sensitisation in certain individuals.
- ! Avoid skin and eye contact.
- ! Handle only when wearing protective clothing.
- ! Wash splashes from the skin with soap and water, flush eyes with copious amounts of water and seek medical attention if irritation persists.



Health & safety information
available on request



Important Disclaimer

The information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice. Please ensure you have the latest updated information.



Sovereign

the gold standard in building products

Sovereign Support: 01229 870800 | www.sovchem.co.uk

FIND US HERE

