



Never compromise on quality!



HIGH STRENGTH BRICK ACID

Strong Hydrochloric Acid Cleaner



BUILDERS COMPLETE RANGE

Description:

An acid based cleaner formulated to remove unsightly stains caused by numerous every day occurrences, as well as builders splatter.

Uses

For removing cement and mortar splashes, light oil stains and grease from brickwork, paving, tiles, earthenware and concrete. Bond It **HIGH STRENGTH BRICK ACID** should not interfere with the various types of concrete and stone (except limestone and marble) commonly encountered in the general building area. Efflorescence can also be removed by using this product diluted.

Application

Gloves, overalls, boots and goggles should be worn at all times during application. Protect metal surfaces and paint-work before application with polythene sheets and tape. Remove excess dirt, mortar, etc. with a stiff yard brush. If cleaning down brickwork saturate area with water to prevent damage to mortar. Before commencing a full clean down, test on an inconspicuous area with Bond It **HIGH STRENGTH BRICK ACID** diluted 4:1, water to cleaner. For normal use dilute between 2 and 4 parts water to 1 part cleaner. Apply using a brush and allow to stand for 10-15 minutes ensuring the area does not dry out and is scrubbed occasionally with a stiff yard brush. Rinse thoroughly with large amounts of water, do not add water to neat cleaner, always add the cleaner to the water. If stains persist, repeat the process and/or use the cleaner undiluted taking care to test the neat cleaner first on an inconspicuous area. For removing efflorescence use a 8:1 dilution water to cleaner. Always use a plastic container for diluting this product.

Limitations

Do not use Bond It **HIGH STRENGTH BRICK ACID** on limestone or marble as the chemicals will attack the surface. This product can also have an adverse effect on coloured concrete, test an inconspicuous area before use.

For removing mould, lichen or mildew, Bond It **MOULD STOP**, **PATIO BLASTER** or **ORGANIC CLEANER** should be used. **HIGH STRENGTH BRICK CLEANER** and its fumes will attack limestone, marble stainless steel and aluminium. If used internally extreme care should be used and thorough ventilation



provided. Do not allow product to come into contact with metals such as steel, copper, aluminium and titanium. If used internally, extreme care must be taken and thorough ventilation provided as fumes can cause damage to sensitive surfaces.

Cleaning of Tools

Rinse equipment after use with plenty of clean water. **Note:** Do not throw rinsing water onto plants/ grass.

Container Size

5L and 25L plastic bottles.

Coverage

Approximately 30-60m² per 5 Litres.

Shelf Life

2 years from date of manufacture when stored in sealed bottles.

Storage Conditions

Store in cool, dry conditions in a sealed container between temperatures of 5 and 30°C. KEEP AWAY FROM CHILDREN. Store away from alkaline products and bleach.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Flammability	Non-flammable
Boiling Point	100°C
Composition	16% hydrochloric acid
UN Class	1789 Hydrochloric Acid
UFI	KC10-Y0QX-Q00K-YNPD

Product Details:

Colour:	Clear	Clear
Code:	BDH085	BDH086
Size:	5L	25L
Barcode:	5060021367464	5060021367440



Part of the Bond It Builders Complete Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001



SCAN ME AND GET THE BOND IT APP

BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 **Fax** +44 (0)1422 315310
Email: salesuk@bonditgroup.com **Website:** www.bonditgroup.com



V5 05/10/18
 Supersedes: V4 19/10/21