

This safety data sheet complies with the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF Supercedes Date: 26-Jul-2022

Revision date 15-Aug-2023 Revision Number 1.06

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product Name	BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF
Pure substance/mixture	Mixture
1.2. Relevant identified uses of th	e substance or mixture and uses advised against
Recommended use	Filler
Uses advised against	None known
1.3. Details of the supplier of the	safety data sheet
Company Name Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36	
E-mail address	SDS.box-EU@bostik.com
1.4. Emergency telephone numbe	<u>'r</u>
United Kingdom	Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri) NHS: 111
SECTION 2: Hazards identi	fication
2.1. Classification of the substant	ce or mixture
GB CLP (SI 2020/1567 as amende	d)
This mixture is classified as not haz	ardous according to regulation (EC) 1272/2008 [CLP]
2.2. Label elements	
This mixture is classified as not haz	ardous according to regulation (EC) 1272/2008 [CLP]
Signal word None	
Hazard statements This mixture is classified as not haz	ardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction EUH210 - Safety data sheet available on request EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust

BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF

Supercedes Date: 26-Jul-2022

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Quartz	238-878-4	14808-60-7	40 - <80	[B]	-	[5]
Titanium dioxide	(022-006-00- 2) 236-675-5	13463-67-7	1 - <5	[C]	-	01-2119489379- 17-XXXX
Quartz (fine fraction)	238-878-4	14808-60-7	0.1- <1	STOT RE 1 (H372)	-	[5]
Ethylene glycol	(603-027-00- 1) 203-473-3	107-21-1	0.1 - <0.5	STOT RE 2 (H373) Acute Tox. 4 (H302)	-	01-2119456816- 28-XXXX
reaction mass of 5-chloro-2-methyl-2H-iso thiazol-3-one and 2-methyl-2H-isothiazol-3 -one (3:1) [C(M)IT/MIT]		55965-84-9	<0.0015	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Eye Dam. 1 :: C>=0.6% Eye Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015%	-

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[B] - Substance with a Community workplace exposure limit [C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF

Supercedes Date: 26-Jul-2022

Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	В
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] - 55965-84-9	

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.
4.2. Most important symptoms and	l effects, both acute and delayed
Symptoms	No information available.
4.3. Indication of any immediate m	edical attention and special treatment needed
Note to doctors	No information available.
SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	No information available.
5.2. Special hazards arising from t	he substance or mixture
Specific hazards arising from the chemical	No information available.
Hazardous combustion products	Carbon oxides.
5.3. Advice for firefighters	
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF Supercedes Date: 26-Jul-2022 Revision date 15-Aug-2023 Revision Number 1.06

6.1. Personal precautions, protecti	ve equipment and emergency procedures
Personal precautions	Ensure adequate ventilation.
For emergency responders	Use personal protection recommended in Section 8.
6.2. Environmental precautions	
Environmental precautions	See Section 12 for additional Ecological Information.
6.3. Methods and material for conta	ainment and cleaning up
Methods for containment	Do not scatter spilled material with high pressure water streams.
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
6.4. Reference to other sections	
Reference to other sections	See section 8 for more information. See section 13 for more information.
SECTION 7: Handling and st	orage
7.1. Precautions for safe handling	_
Advice on safe handling	Ensure adequate ventilation.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice.
7.2. Conditions for safe storage, in	cluding any incompatibilities
Storage Conditions	Keep from freezing.
Recommended storage temperature	Do not freeze.
7.3. Specific end use(s)	
Specific use(s) Filler.	
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.
Other information	Observe technical data sheet.
SECTION 8: Exposure control	ols/personal protection
8.1. Control parameters	
Exposure Limits	This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Quartz	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
14808-60-7		STEL: 0.3 mg/m ³
Limestone	-	TWA: 10 mg/m ³
1317-65-3		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Ashes (residues), cenospheres	-	TWA: 10 mg/m ³

BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF

Supercedes Date: 26-Jul-2022

Revision date 15-Aug-2023 Revision Number 1.06

93924-19-7		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Titanium dioxide	-	TWA: 10 mg/m ³
13463-67-7		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Quartz (fine fraction)	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
14808-60-7		STEL: 0.3 mg/m ³
Ethylene glycol	TWA: 20 ppm	TWA: 10 mg/m ³
107-21-1	TWA: 52 mg/m ³	TWA: 20 ppm
	STEL: 40 ppm	TWA: 52 mg/m ³
	STEL: 104 mg/m ³	STEL: 40 ppm
	*	STEL: 104 mg/m ³
		STEL: 30 mg/m ³
		Sk*

Derived No Effect Level (DNEL)

No information available

Derived No Effect Level (DNEL)			
Quartz (14808-60-7)			
Titanium dioxide (13463-67-7)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m³	

Ethylene glycol (107-21-1)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	106 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	35 mg/m³	

Derived No Effect Level (DNE	L)		
Titanium dioxide (13463-67-7)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

Ethylene glycol (107-21-1)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	53 mg/kg bw/d	
Consumer Long term Local health effects	Inhalation	7 mg/m³	

Predicted No Effect Concentration (PNEC)

BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF

Supercedes Date: 26-Jul-2022

Revision date 15-Aug-2023 Revision Number 1.06

Predicted No Effect Concentration (PNEC) Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

Ethylene glycol (107-21-1)	
Environmental compartment Predicted No Effect Concentration (PNEC)	
Freshwater	10 mg/l
Marine water	1 mg/l
Freshwater sediment	20.9 mg/kg dry weight
Soil	1.53 mg/kg dry weight
Microorganisms in sewage treatment	199.5 mg/l
Freshwater - intermittent	10 mg/l

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	Avoid contact with eyes. Wear safety glasses with side shields (or goggles). Eye
	protection must conform to standard EN 166.
Hand protection	Wear suitable gloves. Gloves must conform to standard EN 374. Ensure that the
	breakthrough time of the glove material is not exceeded. Refer to glove supplier for
	information on breakthrough time for specific gloves. The breakthrough time of the gloves
	depends on the material and the thickness as well as the temperature. Gloves should be
	replaced regularly and if there is any sign of damage to the glove material.
Skin and body protection	Suitable protective clothing.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Appearance Colour Odour	Solid Paste No information available Characteristic.	
Property	Values	Remarks • Method
Melting point / freezing point Initial boiling point and boiling	0 °C 100 °C	
range Flammability	No data available	None known
Flammability Limit in Air Upper flammability or explosive	No data available	None known
limits		
Lower flammability or explosive limits		
Flash point	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm²/s	
Dynamic viscosity	No data available No data available.	None known
Water solubility	INU UALA AVAIIADIE.	

BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF

Supercedes Date: 26-Jul-2022

Revision date 15-Aug-2023 Revision Number 1.06

Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	1.66	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
9.2. Other information		
Solid content (%)	No information available	
VOC content	No da	ita available

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No information available.
10.2. Chemical stability	
Stability	Stable under normal conditions.
Explosion data	
Sensitivity to mechanical	None.
impact Sensitivity to static discharge	None.
10.3. Possibility of hazardous react	tions_
Possibility of hazardous reactions	None under normal processing.
10.4. Conditions to avoid	
Conditions to avoid	Do not freeze.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition None under normal use conditions. Stable under recommended storage conditions. products

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF

Supercedes Date: 26-Jul-2022

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Based on available data, the classification criteria are not met.
Ingestion	Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	>5000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz	>2000 mg/kg (Rattus)	-	-
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus)4 h
Quartz (fine fraction)	>2000 mg/kg (Rattus)	-	-
Ethylene glycol	ATE 500 mg/kg	= 10600 mg/kg (Rattus) = 9530 μL/kg (Oryctolagus cuniculus)	>2.5 mg/L (Rat)6 h
reaction mass of 5-chloro-2-methyl-2H-isothiazo I-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	= 53 mg/kg (Rat)	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	= 0.33 mg/L (Rat) 4h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	Eye			Non-irritant
Acute Eye					
Irritation/Corrosion					

BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF

Supercedes Date: 26-Jul-2022

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Results		
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser		
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Dermal	Not a skin sensitiser		
Germ cell mutagenicity	Based on available data, the	e classification criteria are	not met.		
Carcinogenicity	Based on available data, the	e classification criteria are	not met.		
Reproductive toxicity	Based on available data, the classification criteria are not met.				
STOT - single exposure	Based on available data, the classification criteria are not met.				
STOT - repeated exposure	Based on available data, the classification criteria are not met.				
Aspiration hazard	Based on available data, the classification criteria are not met.				
11.2. Information on other hazards					
11.2.1. Endocrine disrupting properties					
Endocrine disrupting properties	s No information available.				
11.2.2. Other information					
Other adverse effects	No information available.				

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Titanium dioxide	LC50 (96h)	-	-	-		
13463-67-7	>10000 mg/l					
	(Cyprinodon					
	variegatus)					
	OECD 203					
Ethylene glycol	EC50: 6500 -	LC50 96 h =	EC50 = 10000	EC50:		
107-21-1	13000mg/L (96h,	16000 mg/L	mg/L 16 h	=46300mg/L		
	Pseudokirchneri	(Poecilia	EC50 = 620	(48h, Daphnia		
	ella subcapitata)	reticulata static)	mg/L 30 min	magna)		
			EC50 = 620.0			

BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF

Supercedes Date: 26-Jul-2022

			mg/L 30 min			
reaction mass of	EC50 (72h)	EC50 (96h) =	-	EC50 (48h) =0.1	100	100
5-chloro-2-methyl-2H-is	=0.048 mg/L	0.22 mg/L		mg/L (Daphnia		
othiazol-3-one and	(Pseudokirchner	(Oncorhynchus		magna) (OECD		
2-methyl-2H-isothiazol-	iella subcapitata)	mykiss) (OECD		202)		
3-one (3:1)	(OECD 201)	211)				
[C(M)IT/MIT]		,				
55965-84-9						

12.2. Persistence and degradability

Persistence and degradability No information available.

Quartz (14808-60-7)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	biodegradation	Not readily biodegradable
Biodegradability: CO2 Evolution Test	-	-	
(TG 301 B)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Ethylene glycol	-1.36
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	0.7
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	

12.4. Mobility in soil

Mobility in soilNo information available.12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does
	not apply
Ethylene glycol	The substance is not PBT / vPvB PBT assessment does
	not apply
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	The substance is not PBT / vPvB
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused Dispose of in accordance with local regulations. Dispose of waste in accordance with

BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF Supercedes Date: 26-Jul-2022

products	environmental legislation.
Contaminated packaging	Do not reuse empty containers.
European Waste Catalogue	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Keep from freezing.

Land transport (ADR/RID) 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 Environmental hazards 14.6 Special precautions for user Special Provisions	Not regulated Not regulated Not regulated Not applicable None
IMDG	
14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
14.7 Maritime transport in bulk	
according to IMO instruments	
I ransport in bulk according to	Annex II of MARPOL and the IBC Code Not applicable
Air transport (ICAO-TI / IATA-DGR)	
14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	N1
Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF

Supercedes Date: 26-Jul-2022

Revision date 15-Aug-2023 Revision Number 1.06

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed

- H302 Harmful if swallowed
- H310 Fatal in contact with skin
- H314 Causes severe skin burns and eye damage
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage
- H330 Fatal if inhaled
- H372 Causes damage to organs through prolonged or repeated exposure
- H373 May cause damage to organs through prolonged or repeated exposure
- H400 Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'.

In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

Note V: If the substance is to be placed on the market as fibres (with diameter < $3 \mu m$, length > $5 \mu m$ and aspect ratio > 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in

BOSTIK EXPRESS POINTING MORTAR CEMENT BUFF

Supercedes Date: 26-Jul-2022

quantities leading to significant impairment of particle clearance mechanisms in the lung Notes relating to the classification and labelling of mixtures Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm Legend TWA TWA (time-weighted average) STEL (Short Term Exposure Limit) STEL Ceiling Limit Value Ceiling Skin designation SVHC Substance(s) of Very High Concern Persistent, Bioaccumulative, and Toxic (PBT) Chemicals PBT vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals STOT RE Specific target organ toxicity - Repeated exposure Specific target organ toxicity - Single exposure STOT SE EWC European Waste Catalogue European Agreement concerning the International Carriage of Dangerous Goods by ADR Road IMDG International Maritime Dangerous Goods (IMDG) IATA International Air Transport Association (IATA) Regulations concerning the International Transport of Dangerous Goods by Rail RID

Key literature references and sour No information available	ces for data
Prepared By	Product Safety & Regulatory Affairs
Revision date	15-Aug-2023
Indication of changes	
Revision note	SDS sections updated, 3.
Training Advice	No information available
Further information	No information available

This material safety data sheet complies with requirements of UK REACH Regulations (SI 2019/758 as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet