



# Renderer's Stabilising Primer

PRIMES & STABILISES MOST EXTERNAL SURFACES BEFORE RENDERING

Date: 24 August 2020

Fact Sheet No.: TDS01674

## YOUR SMART ADVANTAGES

- Excellent key for render
- Coloured for controlled application
- No mixing, easy to apply

## USES

Bostik Renderer's Stabilising Primer with Plasprime® Technology has been specially developed for the rendering professional. It primes and stabilises most exterior surfaces, prior to the application of new render. It is grey in colour for easy application and contains approximately 20% recycled material. Bostik Renderer's Stabilising Primer is suitable for outdoor use on both porous and non-porous areas to give a surface that dries evenly giving excellent adhesion and a faster, easier finish.

Bostik Renderer's Stabilising Primer has been developed for preparing exterior walls prior to applying render. It can be applied over brick, blocks, concrete, plaster and render. When rendering externally it removes the need for initial scratch coats, only receiving render is required. Bostik Renderer's Stabilising Primer can be used on internal shiny surfaces such as sound glazed tiles before plastering.

## PRODUCT CHARACTERISTICS

Colour	Grey
Form	Viscous liquid
Specific Gravity	0.95 – 1.05 approx.
Composition	Blend of polymers, additives and recycled material
Product Code	30806587 10 litre bucket
Storage/Shelf Life	Store and transport securely in an upright position. Ensure the lid is secure. Store for up to 12 months

from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost.

## TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	Above +5°C (external work should not be completed in poor drying conditions or when rain is imminent)
Coverage	2 – 4m <sup>2</sup> per litre (depending on the porosity and texture of the surface being prepared) As a guide, a 10 litre bucket will cover approximately 20 – 40m <sup>2</sup>
Drying Times	24 hours approx. (depending on ambient conditions)
Cleaning	Clean tools and equipment with water immediately after use. Remove any splashes, as dried product is difficult to remove

## DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Renderer's Stabilising Primer, refer to the relevant Health & Safety Data Sheet, available at [www.bostik.com/uk](http://www.bostik.com/uk).

## PREPARATION

1. Surfaces must be dry, clean, and free from grease, dust and loose material. Mechanically remove any loose or flaking material. Existing internal paint should be checked for soundness and adhesion. Do not apply directly onto wallpaper.
2. Ensure that any surface to be rendered is strong enough to support the weight of the new render.

IMPORTANT: External render must be of the correct mix design for the strength of the background. Bostik Renderer's Stabilising Primer will not make up for defective surfaces and the bond will only be as good as the weakest part of the system. Ensure the substrate is strong enough to support the weight of any renders being applied. Renders should not be more than 10mm in thickness. Bostik are not responsible for failure of an underlying substrate. It is not suitable for use on external painted walls.

#### APPLICATION

3. Apply Bostik Renderer's Stabilising Primer straight from the bucket, with a soft brush to give an even texture over the entire surface.
4. Allow to dry completely. Drying times are dependent on the porosity of the surface and ambient conditions. Bostik Renderer's Stabilising Primer must be protected from rain until fully dry, but is water resistant once dry.
5. Do not apply when temperatures are below, or may fall below 5°C, or when rain is imminent.
6. It is recommended that the primer is left for 24 hours to dry before applying renders.
7. Once dry, apply render or plaster in the usual way.
8. External render must be the correct mix design for the strength of the background.

#### CLEANING

9. Clean tools and equipment with water immediately after use. Remove any splashes, as dried product is difficult to remove.

#### PRECAUTIONS IN USE

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit [www.bostik.com/uk](http://www.bostik.com/uk) for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Renderer's Stabilising Primer, available at [www.bostik.com/uk](http://www.bostik.com/uk).

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	<a href="mailto:customer.service@bostik.com">customer.service@bostik.com</a>
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	<a href="mailto:technical.service@bostik.com">technical.service@bostik.com</a>
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	<a href="mailto:sds.box-eu@bostik.com">sds.box-eu@bostik.com</a>