



High Performance Floor
Coatings and
Re-Surfacing Screens

EPOXY SEALERS

DRYFIX ASBESTOS CEMENT SEALER

- **Epoxy Resin Based - Water Miscible**
- **Rapid Curing in Cold Wet Conditions**
- **Excellent Adhesion**
- **Can be applied to Wet/Dry Surfaces**



EPOXY ASBESTOS CEMENT SEALER is a two-part epoxy resin especially developed for sealing asbestos cement sheeting both flat and corrugated. It is suitable for applications in both dry or wet conditions. To provide a sealed, dust free, strength enhanced asbestos sheet.

USES: It will provide outstanding performance protection in its own right to asbestos cement sheeting but also will provide an excellent sealed/primed base for any subsequent treatment to adhere to. It can be applied in both dry or wet conditions. This sealer is water miscible and can be applied in wet conditions.

PREPERATION: Surfaces must be clean, sound and free from grease, oil and other forms of surface or impregnated contamination.

REPAIR: Fill cracks with Epoxy Filler and deep holes and wide cracks with Epoxy Mortar Lightweight. Use Tack Primer for the Epoxy Mortar Lightweight.

MIXING: Wear Personal Protective Equipment, protective eye glasses and impervious gloves. Empty the entire contents of Pack B (Hardener) into Pack A (Resin) and stir using a mixing paddle in an electric drill on a slow speed for 3 minutes. Ensure you reach the sides and bottom of the container during the mixing process. Having mixed thoroughly use all within 40 minutes. At this stage you can add up to 10l cold water to ease application for airless spray equipment.

Alliance Remedial Supplies Limited

Unit 11-12 Regent Trade Park, Gosport, Hampshire, PO13 0EQ

Tel: 01329 235252, Email: sales@arsstore.co.uk, Web: allianceremedialsupplies.co.uk

VAT: 119 914 303, Co Reg: 07814823





High Performance Floor
Coatings and
Re-Surfacing Screeds

EPOXY SEALERS



APPLICATION:

Roller Application: Pour into a deep paint scuttle and apply with a large paint roller. First paint around the permanent fixtures to avoid the roller from hitting these areas.

Airless Spray: This product can be spray applied. Having mixed the two components together thoroughly, you can dilute the mix with up to 10% cold water. Two coats are normally required for maximum resistance. For best results apply the second application when the first coat is touch dry or within 7 days. Apply thinly. Do not apply too thick and do not allow any puddles to appear.

HEALTH AND SAFETY: Always read Health and Safety Data Sheet prior to handling

PRODUCT DATA

COVERAGE: 44.5 Litres will cover up to 25 square metres depending upon the site conditions that prevail, i.e., the porosity, texture and temperature of the asbestos.

POT LIFE: When fully mixed, approximately 40 minutes @ 20°C. Extended pot life at lower temperatures, reduced at high temperatures.

CURING /HARDENING TIME: Tack free - 12 hours @ 20°C. Full cure - 7 days. Do not use at freezing temperatures.

CHEMICAL RESISTANCE: Resistant to spillages of many chemicals commonly met within industry.

PROPERTIES			
Parameter	Unit	Figure	Method
Hardness	Shore D	13°C, 24 hours	DIN 53505
		23°C, 7 Days	
Bending Tensile Strength	N/mm2	65	EN ISO 178
Tensile Strength	N/mm2	35	EN ISO 527-1
Abrasion Resistance	mg	60	Taber abrasion (CS10, 1000, 1000)
Adhesive Strength	Far exceeds the cohesive strength of asbestos sheeting		

UV RESISTANCE: Some noticeable discolouration (yellowing) will occur when the cured product is exposed to natural daylight.

COLOURS: Clear or Light Grey. For large orders - coloured to your requirements

FLAMMABILITY: Non flammable

SHELF LIFE: 12 months in sealed containers. Protect from frost.

Whilst Alliance Remedial Supplies Limited endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it can not, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification or information given.

Alliance Remedial Supplies Limited

Unit 11-12 Regent Trade Park, Gosport, Hampshire, PO13 0EQ

Tel: 01329 235252, Email: sales@arsstore.co.uk, Web: allianceremedialsupplies.co.uk

VAT: 119 914 303, Co Reg: 07814823